WE MAKE GREEN ENERGY STRONG

Germany Office

Address STRONG Digital GmbH
Von Werth Strasse 1
50670 Cologne
Germany

E-mail info_de@strong-energy.eu
Website www.strong-energy.eu
Call +49 221 2920 1070

Romania Office

Address Strada Emil Racoviță 25,
București 041753
Romania

E-mail contact_ro@strong-energy.eu
Website www.strong-eu.com
Call +40 778 706 799

STRONG Energy

Residential & Portable Energy Storage System

Product Brochure

reddot

BRANCHES

- FRANCE (OPERATIONAL HQ)
- GERMANY
- ROMANIA
- POLAND
- ITALY
- IBERIA (Spain + Portugal)
- AUSTRIA
- UNITED KINGDOM
- TURKEY
- UKRAINE
- SCANDINAVIA (Denmark + Norway + Sweden + Finland + Baltics)
- CEE (Czech + Slovakia)



About STRONG Energy

Strong Energy, as part of the **Strong Group**, has been deeply rooted in the European market **since 1986**, serving more than **20 million European families**. Building on the advantages and experience of its parent company Skyworth in the field of new energies and its locally based European service team, Strong Energy began introducing inverters, energy storage batteries and system solutions in Europe from mid-2023, following the trend of clean energy development to make a positive contribution to global environmental protection.

Strong Energy's parent company **Skyworth** is already world-renowned as a consumer electronics company for its smart TVs, digital set-top boxes and other products. The company employs more than **40,000 people** worldwide, encompasses **20 national high-tech companies** and two publicly listed companies. With its powerful intelligent manufacturing, system integration and supply chain management capabilities, the company entered the household photovoltaic market in 2020, has accumulated more than 5 GW of power plant construction experience and is recording rapid market growth. More than 200,000 household photovoltaic power plants have already been built and connected to the grid in China.

Our Mission

Strong Energy started in mid-2023 with the introduction of inverters, energy storage batteries and system solutions in Europe. We follow the trend of clean energy development and make a positive contribution to global environmental protection – for the present and the future.

Why STRONG Energy?

We Make Green Energy Strong

Service

We give our customers confidence and security based on our high-quality requirements. Our local Germany team offers 360° premium quality in pre-sales and after-sales support.

Experience

As part of the Strong Group, we have been deeply rooted in the European market since 1986, supporting more than 20 million European families. We are a fast-growing group with more than 5 GW of experience in photovoltaic construction from our parent company Skyworth.

Strong Capacity

Our production capacity allows us to manufacture over 20,000 photovoltaic systems in a single month.

Single Source


We offer our customers, tailor-made clean energy solutions and comprehensive services from a single source.



*Pictures may differ from real products

Alfred Three Phase Hybrid All-in-one

CRHxST-10KW | 7.2~24kWh Datasheet



Specification

Model	CRHxST-10KW		
System Parameters			
Number of Batteries	3~10 (Backup power derated when ≤ 4)		
Battery Total Energy	7.2-24kWh		
Degree of Protection	IP65		
Operation Temperature Range	-10℃~55℃		
Allowable Relative Humidity Range	5%~95%		
Max. Operating Altitude	4000m		
Weight (Standard Package)	215.3kg / 6 batteries		
Dimensions (W)x(H)x(D) (Standard Package)	780x1660x240mm / 6 batteries		
Display	APP & LED indicator		
Communication	RS485/CAN (for BMS), RS485, USB, Ethernet, RS485 (for Meter), Optional: Wi-Fi/GPRS/LAN		
Inverter Module			
Nominal AC Output Power	10,000W		
Max. AC Apparent Power	11,000VA		
Max. AC Output Power (PF=1)	11,000W		
Max. AC Output Current	3*16.7A		
Nominal Grid Voltge	3/N/PE, Three Phase 380V / 400V / 415V		
Grid Voltage Range	260V-520V (Adjustable)		
Nominal Output Frequency	50Hz/60Hz		
Nominal Load Output Power	10,000W		
Nominal Load Output Current	3*15.2A		
Peak Output Apparent Power (10S)	15,000VA		
Max. PV Input Power	15,000W		
Max. PV Voltage	1000V		
Start-up Voltage	150V		
MPPT Voltage Range	160V-950V		
Max. Input Current Per MPPT	20A/30A		
Max. Short Circuit Current	30A/40A		
No. of MPPT	2		
Transfer Time	<10ms		
Max. Efficiency (PV to AC)	98.4%		
European Efficiency (PV to AC)	97.9%		
Dimension (W) x (H) x (D)	780x580x240mm		
Weight	47. 3kg		
Battery Module			
Battery Type	LFP	Max.Charge / Discharge Power	2,400W / 2,400W
Rated Energy	2. 4 kwh	Dimension (W) x (H) x (D)	780 x 140 x 240mm
Max.Charge / Discharge Current	50A / 50A	Weight	25 kg
Certification			
Grid	VDE4105, IEC61727/62116, AS4777.2, EN50549-1, C10/11, G98/G100, CEI 0-21, PPDS, RD1699/661/647/413, UNE217002		
Safety	IEC62109-1&2, IEC62477-1		
Warranty	5 Years (10 Years optional)		

Features

All-in-one Integrated



- Guaranteed compatibility between inverter and batteries.
- 1C battery modules for flexibility of capacity as per needs.
- Integrated SwitchBox with ultra reliable power for whole house.
- IP65 enclosure for indoor and outdoor installation.

Advanced Energy Management



- Realtime management on mobile App from anywhere.
- Multiple working modes and flexible customized settings built-in.

Super Silent Furniture-like Design



- Super silent for indoor use.
- Ultrathin design cherishes space integrity.
- Light luxury interior decor aesthetics.

Innovative Easy Installation & Maintainance




- Super easy installation like building bricks.
- Enhanced reliability and easy maintenance.



*Pictures may differ from real products

Alfred High Voltage Stackable ESS
CRJxST-9.6~33.6kWh Datasheet



Specification

Battery Module	
Battery Model	**CR10ST-2400Wh**
Battery Type	LFP (Lithium-ion) 50Ah
Battery Module Capacity	2.4kWh
Module Operating Voltage Range	43.5-54.75Vdc
Max. Charge/Discharge Current	50A/50A
Max. Module Charge/Discharge Power	2,400W/2,400W
Dimensions (W)x(D)x(H)	780x140x240mm
Module Weight	25kg
System Parameters	
System Model	**CRJxST-9.6~33.6kWh**
Battery Scalability	4-14
System Energy	9.6~33.6kWh
System Efficiency	92%
BMS Communication	RS485 / CAN
Protection Category	Class I
Protections	Overvoltage Protection, Overcurrent Protection, Over Temperature Protection, Short-circuit Protection
Cooling Method	Natural Cooling
Ingress Protection	IP65
Operating Temperature	-10°C~50°C (>45°C derating)
Operating Humidity	5%-95%
Storage Temperature	-20°C~45°C
Max. Operating Altitude	4,000m (>2,000m derating)
Certifications	UN38.3, MSDS, IEC62619, VDE-2150, EMC, RoHs

Features

Excellent Power Performance

- 50A Charging / Discharging Current.
- Scalable between 9.6kWh~33.6kWh.
- High Voltage Battery with high efficiency up to 92%.

>10000 Cycles

- Long cycle life with 10000 cycles.
- @ 0.2C discharge to 95% DOD with EOL >65%.

Innovative Batteries

- Small size modularized battery design.
- Wire-free design for easiest installation.
- Flexible battery capacity as per need.

Environmental Nice

- IP65 design for outdoor installation.
- RedDot Awards desigh nice for home decoration aesthetics.

High Reliability


- Reliable Lithium Ion battery adopted.
- Comprehensivice electrical protections.
- Fire suppresion built in battery modules.
- 10 Year Warranty.



*Pictures may differ from real products

Product Image of CRC2SW

EBricks Low Voltage Stackable ESS
CRCxST-5~20kWh Datasheet



Specification

Battery System				
Model	**CRC1ST**	**CRC2ST**	**CRC3ST**	**CRC4ST**
Stacking Method	1	2	3	4
Scalability	5.12 kWh	10.24 kWh	15.36 kWh	20.48 kWh
Nominal Capacity	51.2 Vdc			
Nominal Voltage (Vdc)	40 ~ 58.4Vdc			
Operating Voltage Range (Vdc)	100A / 120A	150A / 150A	150A / 150A	150A / 150A
Max. Charge/Discharge Current	5,000W / 6,000W	10,000W / 12,000W	10,000W / 12,000W	10,000W / 12,000W
Max. Charge/Discharge Power	690 x 160 x 660	690x 160 x 1080	690 x 160 x 1500	690 x 160x 2340
Dimensions (W) x (D) x (H)mm	54.5 kg	102.5 kg	150.5 kg	195.5 kg
System Weight	RS485/CAN			
Communication Method	IP65			
Ingress Protection	Short Term: -20°C~60°C, Long Term: 40% SOC @ 0°C~25°C			
Storage Temperature	Charging: -15°C~55°C (Self-warming when <0°C)			
Opreating Temperature	Discharging: -20°C~60°C			
Opreating Ambient Humidity	5% - 95% (No Condensation)			
Operating Altitude	＜2,000m			
Certification	IEC62619 / UN38.3 / CE-EMC / IEC60730-1			

Battery Module	
Battery Type	LFP
Rated Capacity	5.12kWh
Rated Voltage	51.2Vdc
Operating Voltage Range	40 ~ 58.4Vdc
Max. Charge/Discharge Current	100A / 120A
Dimension (W) x (D) x (H)	690 x160 x 450/420 mm
Weight	48 kg

Features

Excellent Power Performance

- High performance LFP battery cells.
- 5kWh single battery pack, scalable upto 20kWh.
- Wire-free modular design for super easy installation.

Smart Management

- RS485/CAN communication with inverter for remote management.
- Direct connection to internet for remote upgrade and maintanance.

Environmental Adaptive

- IP65 protection for indoor and outdoor.
- Operating temperature -15°C~ 55°C.
- Ultra-thin 160mm thickness saving space.

Quallity Guarenteed

- 5 Year Warranty (10 year optional)

Reliable BMS

- Robust Battery Management System ensures stable and long term operation.
- Comprehensive safety mechnism built-in.



*Pictures may differ from real products

Mini-EBricks Low Voltage Stackable ESS
CRMxST-5kWh~15kWh Datasheet



Specification

Battery Stack	
Battery Type	LFP
Battery Capacity	2.56kWh per module (stackable from 2 to 6)
Max. Charge/Discharge Power per battery pack	2500W/2500W
Max. Charge/Discharge Current per battery pack	50A/50A
Rated Battery Voltage (Pack & Stack)	51.2Vdc
Battery Distribution Unit (BDU)	120A with DC Breaker
Cycle Life	6000 cycles @25℃ with 0.5C DOD-90% EOL-70%
Fire Suppression System	Aerosol Extinguisher Embeded
Ingress Protection	IP65
Operating Temperature	Charge: -10~50℃, Discharge: -20~55℃
Dimension (W)x(H)x(D)	BDU: 380x330x180mm
	Battery pack: 380x340x243mm
	Base: 380x340x100mm
Weight	25kg per pack
Battery Distribuition Unit	
Rated DC Voltage	52 Vdc
Rated DC Current	120 A
Communication	RS485/CAN
DC Breaker	Yes
Display	LED Indicator
Operating Temperature	-20~60℃
Dimession (W)x(H)x(D)	380x180x330mm

Features

Easy & Flexible Installation

- Lightweight, stackable 25kg modules, supporting floor-standing or wall-mounted placement for effortless one-person setup anywhere in the home.

Ultimate Home Safety

- Grade A battery cells with highly reliable BMS, further enhanced by built-in aerosol fire protection in every module for total peace of mind.

Customizable Visual Design

- Tailored decorative panels, perfectly matching personalized home aesthetics.

High-efficiency Performance


- High 0.75C charge/discharge rate, enabling greater power output while optimizing overall system cost.



*Pictures may differ from real products

Product Image of MAX LV

Max LV 16kWh Battery ESS
CR12ST-16KWH Datasheet



Specification

System Parameters	
Battery Type	$LiFePO_4$
Rated Capacity	16.076kWh
Usable Capacity	15.272 kWh (DOD 95%, 0.5C)
Rated Voltage	51.2V
Operating Voltage Range	40~58.4V
Rated Charging Current	150A
Rated Discharging Current	150A
Max. Pulse Dicharging Current	300A @1s
Balancing Method	Passive Balancing
Cycle Life	≥8000 cycles @ 25°C with 0.5C 70%EOL
Communication	RS485/CAN
Operating Temperature	Charging:-20°C~55°C / Discharging: -20°C~60°C
Storage Temperature	-20°C~45°C
Operating Humidity	5~95%
Operating Altitude	≤3000m
Thermal Management	Natural Cooling / Active Warming
Ingress Protection	IP65
Parallel Connection	≤8
Indicator	LED (showing SOC and charging status)
Remote Management	Over-the-air upgrade, Realtime management via App & Web
General Information	
Weight	Approx. 125kg
Dimension (W)x(D)x(H)	550x266x863mm (With wheels) Loading capacity: 108 PCS per 20' GP container
Mounting Method	Floor-Stand (with lock castors)
Certification	UN38.3, MSDS, IEC62619, EMC, etc.

Features

Excellent Performance

- 16.076kWh Capacity with 314Ah.
- 8000 Cycle Life with EOL 70% @0.5C.
- 0.5C Charge/0.5C Discharge Performance.
- Parallel Connection up to 8 units / 128kWh.

Smart Manage

- Realtime monitoring via App & Web.
- RS485/CAN to inverters.
- Passive Balancing.
- Over-the-air upgrade.

Safety

- High reliable lithium battery cell adopted.
- Advanced BMS integrated for realtime monitoring and protection.
- Aerosol fire suppresion unit optional for enhanced safety.

Applicability

- IP65 design perfectly fits wide range of operating environment.
- Lock castors ensures easy moving while installation.


Reliability

- Natual Cooling with higher efficiency and longer life span.
- Commprehensive electrical protection design avoiding danger from lightening, over voltage/current, leakage, electrostatic interference, etc.



Niels Three Phase Hybrid Inverter

CVGMSW-20KW3P/CVGNSW-30kW3P Datasheet



Specification

Model	CVGMSW-20kW3P	CVGNSW-30kW3P
On-Grid AC		
Nominal AC Output Power	20,000 W	30,000 W
Max. AC Apparent Power	22,000 VA	33,000 VA
Max. Single Phase Power	10,000 W	11,000 W
Max. AC Output Current	3 * 33.4 A	3 * 50.1 A
Nominal Grid Voltage	380V / 400V / 415V, 3L+N+PE	
Grid Voltage Range	260V - 520V (Adjustable)	
Nominal Output Frequency	50Hz / 60Hz	
Off-Grid AC		
Nominal AC Output Power (Off-grid)	20,000 W	30,000 W
Max. Single Phase Power	10,000 W	11,000 W
Nominal Output Current (Off-grid)	3*30.3 A	3*45.5 A
Nominal Output Voltage (Off-grid)	380V / 400V / 415V, 3L+N+PE	
Nominal Output Frequency (Off-grid)	50Hz / 60Hz	
Transfer Time	< 10ms (tipical)	
PV Input		
Max. PV Input Power	30,000 Wp	45,000 Wp
MPPT Voltage Range	160 ~ 950 V	
Max. PV Voltage	1,000 V	
Start-up Voltage	150 V	
No. of MPPT	2 (2/2)	3 (2/2/2)
Max. PV Input Current per MPPT	30A / 30A	30A / 30A / 30A
Max. Short Circuit Current per MPPT	40A / 40A	40A / 40A / 40A
Battery		
Battery Type	LFP (Lithium-ion)	
Battery Voltage Range	150V-800V	
Max. Charge/Discharge Current	50A / 50A	
Max. Charge/Discharge Power	24,000W / 22,680W	30,000W / 34,000W
General		
Efficiency	Max. (PV to AC): 98.2%, Euro. (PV to AC): 97.9%, Max. (BAT to AC): 98.0%	
Protection Category	Class I	
Protections	Anti-islanding, AC Over Voltage/Current Protection, AC Short-circuit, DC Reverse, Leakage Current, PV Insulation Detection, SPD DC Type II, AC Type II, AFCI, RSD	
Display & Management	LCD & Wireless & APP & Cloud	
Cooling Method	Natural Cooling	
Ingress Protection	IP66	
Operating Temperature	-25℃ ~ 60℃ (>45℃ derating)	
Operating Humidity	0% ~ 100%	
Dimensions (W)x(D)x(H)	660x570x230mm	

Remarks: The range of output voltage and frequency may vary depending on different grid codes. Specifications are subject to change without advanced notice.

Features

High Reliability

- Key components from international renowned brands.
- IP66 protection rating, ensuring adaptability to complex outdoor environment.
- Multiple built-in protections, with optional AFCI.

Intelligent Maintenance

- Quick commission via mobile app, 24/7 remote monitoring, configuration and upgrade.
- Advanced energy management mechanism, with multiple built-in working modes and flexible customized settings.

Excellent Performance


- Maximum efficiency of 98.4% and battery efficiency of 98.0%.
- Large MPPT current, compatible with high-power solar panels.
- Supporting continuous overload capacity of 110% and unbalanced output.
- Maximum battery charge/discharge current of 2*75A.
- Advanced parallel function.



Pictures may differ from real product

Stanley Single Phase Hybrid Inverter

CVM6ST-6KW Datasheet



Specification

Model	CVM6ST-6KW
Efficiency	
Max. Efficiency (PV to AC)	97.3%
Eur. Efficiency (PV to AC)	96.8%
Max. Efficiency (BAT tO AC)	94.3%
Input (PV)	
Max.PV Input Power	10,000W
Max. PV Voltage	550V
Start-up Voltage	90V
MPPT Operating Voltage Range	70V-540V
Max. Input Current per MPPT	18A/18A
Max. Short Circuit Current per MPPT	20A/20A
String per MPPT	1/1
Nos. of MPPT	2
Input/Output (BAT)	
BatteryType	Lithium-ion/Lead-acid
Nominal Battery Voltage	48V
Battery Voltage Range	40V-65V
Max. Charge/Discharge Current	135A/135A
Max. Charge/Discharge Power	6,000W/6,000W
Output (Grid)	
Nominal AC Output Power	6,000W
Max. AC Output Apparent Power	6,600VA
Max. AC Output Power (PF=1)	6,000W
Max. AC Output Current	28.7A
Nominal Grid Voltage	220V/230V/240V, L+N+PE
Grid Voltage Range	150V-300V (Adjustable)
Nominal Grid Frequency	50Hz/60Hz
Grid Frequency Range	45Hz-55Hz / 55Hz-65Hz (Adjustable)
Power Factor	>0.99 @rated power (Adjustable 0.8 LD-0.8 LG)
THDI	<3% (Rated Power)
Output (Backup)	
Nominal Output Power	6,000W
Nominal Output Current	27.3A/26.1A/25.0A
Peak Output Apparent Power	120% @ 1min, 166% @ 10s
Nominal Output Voltage	220V/230V/240V, L+N+PE
Nominal Output Frequency	50Hz/60Hz
Transfer Time	<10ms (typical)
THDV	<3% @100% R Load
Certification	
Safety	IEC/EN 62109-1&2
Grid	IEC 61727/62116/61683/60068, G98/G99/G100, VDE4105, EN50549-1/-10, CEI 0-21, C10/11
Warranty	5 Years (10 Years optional)

Protection	
Protection Category	Class I
DC Switch	Yes
Anti-islanding Protection	Yes
AC Overcurrent Protection	Yes
DC/AC Overvoltage Protection	DC Type II, AC Type III
AC Short Circuit Protection	Yes
DC Reverse Protection	Yes
Surge Arrester	DC Type III, AC Type III (Type II Optional)
Insulation Resistance Detection	Yes
Leakage Current Protection	Yes
Generator	Optional
General	
Max. Operating Altitude	4000m (>2000m derating)
Ingress Protection Rating	IP65
Operating Temperature Range	-25°C~60°C (>45°C derating)
Relative Humidity	0-100%
Cooling Method	Natural Cooling
Mounting	Wall bracket
Dimensions (W)x(H)x(D)	377x452x206mm
Weight	20kg
HMI & COM	
Display	Bluetooth & APP + LCD
Communication Interface	RS485/CAN (for BMS), RS485,
	Ethernet, DRM/RS485 (for Meter),
	Optional: Wi-Fi/LAN

Remarks: The range of output voltage and frequency may vary depending on different grid codes. Specifications are subject to change without advanced notice.

Features

Excellent Performance

- Support high power PV panel with 18A PV input current.
- Max battery charge/discharge current of 135A.
- Continuous 110% of nominal AC power.



High Flexibility

- Support 40-65V Lithium or Lead-acid battery.
- Max. 9 units parallel for on-gird and off-gird operation.
- Support generator/smart load/AC coupling.
- Plug and play for easy installation.




Safety & Reliability

- IP65: Indoor or outdoor installation.
- Seamless transition to backup mode, for protection against power outages.
- Multiple built-in protections.



Intelligent Maintenance


- Intelligent Management, local & remote monitoring.
- 3 application modes, mixed with battery scheduling.
- 4.3" LCD color touchscreen, easy to operate.





Pictures may differ from real products

Porter Single Phase String Inverter
CVV1ST-3K68 Datasheet



Specification

Model	CVV1ST-3K68
Efficiency	
Max. Efficiency	98.2 %
European Efficiency	97.3 %
Input (PV)	
Max. Input Voltage	550 V
Max. PV Configuration (STC)	150 %
Rated Input Voltage	360 V
Max. Input Current	30A (2*15A)
Max.Short Circuit Current	40A (2*20A)
Start Input Voltage	90 V
MPPT Operating Voltage Range	70V - 540V
Max. Number of PV Strings	2 (1/1)
No. of MPPTs	2
Output (Grid)	
Rated AC Active Power	3680 W
Max. AC Apparent Power	4048 VA
Max. AC Active Power (PF=1)	4400 W
Max. AC Output Current	18.4 A
Rated AC Voltage	220V / 230V / 240, L+N+PE
AC Voltage Range	160V - 300V(Adjustable)
Rated Grid Frequency	50Hz / 60Hz
Grid Frequency Range	45Hz - 55Hz / 55Hz - 65Hz (Adjustable)
THDI	< 3% (Rated Power)
DC Current Injection	< 0.5% In
Power Factor	> 0.99 Rated Power (Adjustable 0.8 LD - 0.8LG)

Protection	
DC switch	Support
Anti-islanding protection	Support
AC overcurrent protection	Support
AC short circuit protection	Support
DC reverse connection	Support
Surge Arrester	AC Type III (Type II optional) /
	DC Type III (Type II optional)
AFCI	Support
Insulation detection	Support
Leakage current protection	Support

General	
Topology	Transformerless
IP Rating	IP65
Night Self Consumption	< 1W
Cooling	Natural Cooling
Operating Temperature Range	-25℃ ~ 60℃
Relative Humidity Range	0 - 100%
Max. Operating Altitude	4000 m
Noise(typical)	30 dB
Dimensions (W) x (H) x (D)	350 x 347 x 137mm
Weight	8.5 kg

HMI & COM	
Display	Wireless & APP， LCD
Communication	Optional: WiFi / GPRS / RS485 / LAN
Certification	
Safety	IEC 62109-1, IEC 62109-2
Grid Code	DE-AR-N 4105, EN 50549-1, CEI 0-21, UNE 2110001/217002, IEC 61727/62116,IEEE 1547, UL 1741,AS 4777, VDE 0126-1
Warranty	10 Years

Features

Excellent Performance

- Maximum efficiency of 98.2%.
- Large string current, compatible with large PV modules.
- Wide voltage rage, compatible with various power grids.

High Reliability

- IP65 protection level for outdoor installation.
- AFCI function integrated to keep safty.
- IP65 Protection adaptable for both indoor and outdoor environment.

Intelligent Maintenance

- Power consumption monitoring.
- Remote configuration and upgrade.
- Quick commissioning via mobile APP.



*Pictures may differ from real products

Product Image of U1800 Pro

Portable Power Station

Basic & Pro Series Datasheet

Specification



Model	U2400 Pro	U1800 Pro	U800 Pro	S-2400	S-1800	S-800
Capacity	**2048Wh**	**1024Wh**	**512Wh**	**2048Wh**	**1024Wh**	**512Wh**
Rated Power	**2400W**	**1800W**	**800W**	**2400W**	**1800W**	**800W**
Ultra Drive	3000W	2400W	1200W	3000W	2400W	1200W
AC Output	2 x 2400W	2 x 1800W	2 x 800W	5 x 2400W	5 x 1800W	2 x 800W
USB-C	1 x 100W	1 x 100W	1 x 100W	1 x 100W	1 x 100W	1 x 100W
	1 x 140W	1 x 140W	1 x 140W	1 x 140W	1 x 140W	1 x 140W
Mains Electricity Input	2400W, ≈65minutes	1200W, ≈58minutes	550W, ≈99minutes	2400W, ≈65minutes	1200W, ≈58minutes	550W, ≈99minutes
Solar Input	800W, ≈3hours	500W, ≈2.4hours	220W, ≈2h	800W, ≈3hours	500W, ≈2.4hours	220W, ≈2h
Car Charger Input	126W, ≈20hours	126W, ≈10hours	126W, ≈3.5h	126W, ≈20hours	126W, ≈10hours	126W, ≈3.5h
Cell	The capacity of LFP (Lithium Iron Phosphate) is over 80% even after 4000 cycles of usage					
BMS	√	√	√	√	√	√
EPS	20ms	20ms	20ms	20ms	20ms	20ms
APP	√	√	√	√	√	√
Dimension (W) x (H) x (D)	210x309.5x455mm	210x309.5x350mm	185×230×200mm	210x309.5x455mm	210x309.5x350mm	185×230×200mm
Weights	≈22.1kg	≈14.3kg	≈7.35kg	≈22.1kg	≈14.3kg	≈7.35kg
Lights	√	√	√	√	√	√
Audio	Hi-Fi Level Audio	Hi-Fi Level Audio	Hi-Fi Level Audio	--	--	--
Voice-activated	AI Intelligent Voice	AI Intelligent Voice	AI Intelligent Voice	--	--	--
Screen	4.3-inch TFT	4.3-inch TFT	4.3-inch TFT	4.3-inch LCD	4.3-inch LCD	4.3-inch LCD
Warranty	2-year	2-year	2-year	2-year	2-year	2-year

Features

Artistic Design

Red Dot Award 2024
Sleek Design, Pure Aesthetics

Hi-Fi Level Audio[4.]

60Hz-20kHz Frequency Response
DSP-Enhanced Virtual Surround
Bluetooth 5.3 with Dual Connectivity

4.3-inch TFT Display[4.]

Stunning Visual Experience
Responsive Touch Control
Intuitive Multi-Interface

LFP & BMS 4000+Cycles

Ensuring Ultimate Safety
4000 Cycle Lifespan,
Durable for 10+ years
Advanced BMS protection

Ultra High Power

Rated 1800W | Peak 2400W
Runs 99% Household Devices [1.]

3 Charging Options

AC Outlet ≈58 min[2.]
Solar Input ≈2.2h[2.]
Car Charger ≈10h[2.]

EPS Emergency Backup

EPS with 20ms Response

App Control

Remote Monitoring
Real-Time Control

Easy to Carry

14% Size Reduced[3.]
One Hand Control

2-Year Global Warranty

2-Year Quality Guarantee
Free Repairs for Main Components

Data from Skyworth Labs. 1. 99%=Common Household Devices 2. Volume vs Industry Average 3. Charge Time with 400W Solar Panel 4. Function only for Pro series.



15000mAh Airline Safe

*Pictures may differ from real products

Airline Safe

VETA 29 Ultra-charge Power Bank
15000mAh Datasheet

Specification

Model	S-29	Low Current Mode	Support
Capacity	15000mAh	Fast Charging Protocol	UFCS, QC3/QC5, FCP, SCP, AFC,
Battery Type	18650 Lithium Ion INR 18650/25P		PD3.0/3.1, DCP, PPS, Apple 2.4A, VOOC
Interface	Type-C1 (140W) IN/OUT (Cable)	Temperature Test	3000 times per minute
	Type-C2 (100W) IN/OUT	Number of Cycles	≥60% after 300 cycles
	USB-A (24W) OUT	Operating Temperature	-20℃~60℃
Maximum Output per Port	140W	Shell Material	VO PC
Maximum Total Output Power	205W	Charging Cable	Built-in 26cm 140W cable
Charging Time	Full charge in 29 mins with 140W charger	Weight	420g
Screen	1.3-inch TFT color screen	Size	152x46x45mm

≈29min*
Fully Charged

*The above data is based on Skyworth laboratory conditions. A 140W power adapter supporting the PD 3.1 protocol is required to achieve a full self-charge in approximately 29 minutes. Actual charging duration may vary depending on environmental conditions and operating states.



Sleek Design
Built-in 140W USB-C Cable



205W Max
Total Output
One Solution for All Your Devices



15000mAh
Capacity

Compatible with PD3.1 & UFCS Protocols
Power 1000+ Devices



Ultra-Wide
Operating Temperature Range
-20℃~45℃



Power Status at a Glance
Full-Color HD
Smart Display



Airplanes &
High-Speed Trains
Travel-Ready





*Pictures may differ from real products

GaN Charger
C-140W Datasheet

Specification

Model	C-140W
Input	100-240V~50/60Hz 2A
USB-C1 Output	5.0V⎓3.0A/9.0V⎓3.0A/12.0V⎓3.0A/15.0V⎓3.0A/20.0V⎓5.0A/28.0V⎓5.0A (140W Max.)
USB-C2 Output	5V⎓3.0A/9V⎓3.0A/12V⎓3.0A/15V⎓3.0A/20.0V⎓5.0A (100W Max.)
USB-C3 Output	5.0V⎓3.0A/9.0V⎓3.0A/12.0V⎓2.5A/15V⎓2A/20V⎓1.5A (30W Max.)
USB-A Output	5V⎓3A/9V⎓2A/11V⎓25A/12V⎓1.5A (22.5W Max.)
Dimensions	67x38x74 mm
Weight	290g


AI Intelligent Display Window


Eye-Catching Original Design That Delights



Smart Charging Guidance

Real-Time Port Recommendation for Optimal Charging





4-Port Charging

Up to 140W Max Output



Triple Intelligent Temperature Control

Potting Process
AI Temperature Regulation
Active Cooling

One Charger for the World

Swappable Plug
Global Voltage Support



Fast Charging Compatibility

UFCS/QC3.0/QC5.0/FCP/SCP/ AFC/PD3.0/PD3.1



Powered by

Next-Gen GaN Technology



Firm Wall Plug

Stays Securely in Place



Slim & Portable

Effortless Storage



Foldable Solar Panel

110W / 220W / 400W Datasheet

Specification

Model	110W	220W	400W
Unfolded Dimensions (excluding cable and bag)	1772±5x430±2x2.3±0.5mm	2106±5x602±3x2.3±0.5mm	2463±5x928±3x3.2±0.5mm
Folded Dimensions (excluding cable and bag)	455±5x430±2x35±5mm	605±5x523±3x40±5mm	928±5x630±3x29±5mm
Folding Quantity		4 folds	
Battery Type		TOPcon monocrystalline silicon cells	
Maximum Power	110W	220W	400W
Net Weight (single product including cable)	3.3±0.4kg	5.2±0.5kg	7.4±0.5kg
Photoelectric Conversion Efficiency		≈25%	≈25%
Open Circuit Voltage	22.4V	21V	58.8V
Operating Current	6.0A	12.2A	8.1A
Short Circuit Current	6.3A	12.8A	8.5A
Operating Temperature		-20°C to 60°C	
Warranty		12 months	


Sun Tracker
3s Quick Setup
Charge at Max Speed




IP68
Waterproof
Storm & Dust Proof




3 Angle Adjustments
Optimize Sunlight
Set Stand to **55°, 45°, 35°**





Max Compatibility
Designed for **STRONG**
Portable Power Station

25% Conversion Rate
Advanced TOPcon Tech
Faster Charging



Portable & Foldable
4X Compact Folding
Thinner, Lighter
Built-in Tool Kit



Plug-and-Play
MC4 to XT60 Adapter
Compatible with
Most Portable Power Station



Multi-Panel Linking
Speed Boost



Sleek Design
Oxford Fabric Leather Handles
Strong Clasps



Pictures may differ from real products