



DEC 63 FEELGOOD SKIN



DATA SHEET

Product description

Feelgood Skin is a dual-function technology: bipolar capacitive radiofrequency with two differently sized heads; low-frequency ultrasound for deep cleansing of the skin and delivery of active ingredients.

RADIOFREQUENCY FUNCTION: bipolar electromagnetic waves act on the surface layers of the skin, activating fibroblasts and stimulating the production of new collagen and elastin. What are the effects?

- **Natural lifting**
- **Plumping and moisturising action**
- **Smoothing of superficial wrinkles**
- **Skin tightening**

ULTRASOUND FUNCTION: it works by exploiting the combination of two currents: galvanic and low-frequency ultrasound. What are the effect?

- **Deep skin cleansing**
- **Cell regeneration**
- **Reactivating micro massage**
- **Oxygenating and exfoliating action**

The Tablet is the user interface: it is possible to select commands even remotely, making it easier for the operator to select parameters with both visual and vocal assistance.

Accessories



AC0661
Power cable



AC0710
Tablet



AC0674
Spatula
ultrasound



AC0672
Electrode



AC0665
Electrode cable



AC0707
RF Head holder
handpiece



AC0704
RF Bipolar head
for face



AC0704P
RF Bipolar head
for small areas



JML19
Trolley

Technical specifications

PRODUCT NAME	FEELGOOD SKIN
PRODUCT DESCRIPTION	Ultrasound stimulator and capacitive bipolar radiofrequency to treat skin blemishes on face, hands and décolleté
PRODUCT CODE	DEC 63
CATEGORY	Ultrasound stimulator, mechanical vibration peeling and partial heat treatment using bipolar capacitive RF
DIMENSIONS	Device dimensions: 29x25x37,5 cm Net Weight: 5 kg Trolley dimensions: 75,5 x 40 x 79 cm (LxPxH) Trolley weight: 8 kg
GENERAL TECHNICAL SPECIFICATIONS	Power supply: 230Vac - 50Hz Maximum consumption: 200 Watt Fuses: 2x 4 AT
GENERAL CHARACTERISTICS	PROTECTION CLASS: I APPLIED PART: TYPE BF

Technical specifications

LOW-FREQUENCY ULTRASOUND	Resistance: Max 400 Ω Frequency: 25 kHz \pm 5 kHz Max output power: 1,5 W/cm ² Capacity 20500 pF \pm 20% Operating modes: continuous and pulsed
BIPOLAR CAPACITIVE RF	Max voltage: 400 Vpp Frequency: 1000 kHz (1 Mhz) Max output power: 50 Watt capacitive @ 50 ohm Emission type: capacitive Emission characteristic: bipolar Automatic applicator recognition system: YES
USER INTERFACE	Tablet

MADE IN **ITALY**



CE MARKING IN ACCORDANCE WITH EUROPEAN COMMUNITY DIRECTIVES

Decomedical by Jean Marie Lorenz s.r.l.

Via Lauro, 5, 84090 - San Mango Piemonte - ITALY

Phone: +39 089 631 094

decomedical@decomedical.com

www.decomedical.com



Company with Management Quality System certified in accordance with
ISO 9001:2015 and ISO 13485:2016.

