

HAELink Supply Inc.

ROUND SPEAKER CABLE

22 AWG - 14 AWG | 2C - 4C | 300 V | 75°C



Product Description

Multi-conductor round speaker cable for audio/sound, control, instrumentation and LED lighting applications. Available with PVC or LSOH construction. HAELink product range: 22 AWG through 14 AWG, 2 to 4 conductors.

General Specifications

Property	Specification
Conductor Size Range	22 AWG - 14 AWG
Number of Conductors	2C - 4C
Conductor	Stranded copper
Operating Temperature	75°C
Voltage Rating	300 V
Material	PVC / LSOH
Construction	Round multi-conductor cable

Reference Construction Data

AWG	Cores	Conductor	Insulation	OD
20 AWG	2C	26 / 0.16	1.6 mm	4.0 mm
18 AWG	2C	17 / 0.255	1.8 mm	4.4 mm
16 AWG	2C	26 / 0.255	2.2 mm	5.6 mm
14 AWG	2C	41 / 0.255	2.8 mm	6.9 mm
20 AWG	4C	26 / 0.16	1.6 mm	4.8 mm
18 AWG	4C	17 / 0.255	1.8 mm	5.4 mm
16 AWG	4C	26 / 0.255	2.2 mm	6.8 mm
14 AWG	4C	41 / 0.255	2.8 mm	8.4 mm

Applications

Audio / sound systems • Control circuits • Instrumentation • LED lighting

Note: The supplied reference table provides dimensional data for 20, 18, 16 and 14 AWG in 2C and 4C. HAELink's stated range also includes 22 AWG and intermediate 3C constructions, but dimensions for those configurations were not provided in the source and are therefore not assumed in this sheet.