

Luminary Commit Primer

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 9/24/2024 Revision date: 4/24/2025 Supersedes: 9/24/2024 Version: 1.1

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : Luminary Commit Primer

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Professional use only, external use only, keep out of the reach of children

1.4. Supplier's details

VanDahl Inc.
350 Sunpac CT. Suite 2
Henderson , NV 89011
T 702-553-6463
info@luminarynailsystems.com

1.5. Emergency phone number

Emergency number : For Hazardous Materials or Dangerous Goods Incident
Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC
Day or Night: 1-800-424-9300 (Toll Free, USA) /
703-527-3887 (Virginia, USA) CCN 1018977

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquid, Category 2	H225	Highly flammable liquid and vapor.
Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.

Full text of H statements : see section 16

Luminary Commit Primer

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)

:



Signal word (GHS US)

:

Danger

Hazard statements (GHS US)

:

Highly flammable liquid and vapor
May cause an allergic skin reaction
Causes serious eye damage
May cause drowsiness or dizziness

Precautionary statements (GHS US)

:

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
Keep container tightly closed.
Ground/Bond container and receiving equipment.
Use explosion-proof electrical, lighting, ventilating equipment.
Avoid breathing mist, spray, vapors.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves, protective clothing, eye and face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If skin irritation or rash occurs: Get medical advice or attention.
Take off immediately all contaminated clothing and wash it before reuse.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center or doctor.
Call a poison center or doctor if you feel unwell.
In case of fire: Use Dry chemical, CO₂, alcohol-resistant foam or waterspray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Keep cool.
Store locked up.
Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

Luminary Commit Primer

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Ethyl acetate	CAS-No.: 141-78-6	75 – 90	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
2-Hydroxyethyl methacrylate	CAS-No.: 868-77-9	< 10	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
2,2-bis-(4-(2-hydroxy-3-methacryloxypropoxy) BIS-GMA	CAS-No.: 1565-94-2	≤ 10	Eye Dam. 1, H318 Skin Sens. 1, H317

Full text of hazard classes and H-statements : see section 16

Luminary Commit Primer

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Call a physician immediately. First aider: Pay attention to self-protection. Never give anything by mouth to an unconscious person. Give artificial respiration if necessary. Induce artificial respiration with mask fitted with one-way valve or other suitable device but not mouth-to-mouth.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim is unconscious : Lay in a stable manner on victim's side. Induce artificial respiration with mask fitted with one-way valve or other suitable device; not mouth-to-mouth. Call a physician immediately.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin areas with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately transport the casualty to an eye doctor / hospital. Continue rinsing during the transport with isotonic saline solution, alternatively with water.
First-aid measures after ingestion	: Rinse mouth out with water. Do NOT induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. May cause skin irritation.
Symptoms/effects after eye contact	: Serious damage to eyes. Stinging, redness, itching, tears, blurred vision, swelling.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract.
Most Important Symptoms/Effects	: Risk of serious damage to eyes.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: IF exposed: Call a POISON CENTER or doctor/physician.
-----------------------------------	---

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Dry chemical, CO ₂ , alcohol-resistant foam or waterspray.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.
Explosion hazard	: Vapors may cause fire/explosion if source of ignition is present.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide. Nitrogen oxides.

5.3. Special protective equipment and precautions for fire-fighters

Luminary Commit Primer

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

- | | | |
|--------------------------------|---|---|
| Firefighting instructions | : | Evacuate area. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection. Move containers from fire area if it can be done without personal risk. Cool affected containers with flooding quantities of water. Withdraw immediately in case of rising sound from venting devices or discoloration from tank. For a massive fire, use unmanned hose holders or monitor nozzles, or withdraw from the area and allow fire to burn. Prevent fire-fighting water from entering environment. |
| Protection during firefighting | : | Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | | |
|------------------|---|--|
| General measures | : | Avoid all personal contact including breathing in the mist, spray, vapors. Do not take actions involving personal risks. Absorb spillage to prevent material-damage. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. |
|------------------|---|--|

For non-emergency personnel

- | | | |
|----------------------|---|--|
| Protective equipment | : | Wear recommended personal protective equipment. |
| Emergency procedures | : | Evacuate the danger area. If outdoors, move to an area upwind of the danger area. Avoid breathing mist, spray, vapors. Avoid contact with skin and eyes. Prevent other non-emergency personnel from entering the danger area. If possible without taking personal risks, remove ignition sources, ventilate area. No open flames, no sparks, and no smoking. |

For emergency responders

- | | | |
|----------------------|---|--|
| Protective equipment | : | Wear the recommended personal protective equipment. Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : | Evacuate personnel to a safe area. Do not touch spilled material. Consider the risk of potentially explosive atmospheres. All equipment used when handling the product must be grounded. Stop leak if safe to do so. Remove all sources of ignition. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. |

- | | | |
|---------------------------|---|---|
| Environmental precautions | : | Do not let the product reach soil, drains, sewers, or surface and ground water. |
|---------------------------|---|---|

6.2. Methods and materials for containment and cleaning up

- | | | |
|-------------------------|---|--|
| For containment | : | Contain with non-combustible inert absorbent. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk. |
| Methods for cleaning up | : | Take up in non-combustible inert absorbent and place into container for disposal. Contaminated absorbent material may pose the same hazard as the spilt product. Decontaminate surfaces and equipment with water and detergent. Until a sufficient level of dilution is achieved, the decontamination water may pose the same hazards as the product. Notify authorities if product enters sewers or public waters. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations. |

For further information refer to section 8: "Exposure controls/personal protection", For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Luminary Commit Primer

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Precautions for safe handling	: Use only outdoors or in a well-ventilated area. Wear personal protective equipment. Avoid breathing mist, spray, vapors. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Use only non-sparking tools. Use explosion-proof equipment. Flammable vapors may accumulate in the container.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.
Additional hazards when processed	: Proper grounding procedures to avoid static electricity should be followed. Vapor/air mixtures are explosive.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions	: Store in a cool, dry and well-ventilated area away from incompatible substances. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Keep container tightly closed. Use explosion-proof equipment.
Incompatible materials	: Strong acids. Strong bases. Strong oxidizing agents. Nitrates. Peroxides.
Heat-ignition	: No flames, no sparks. Eliminate all sources of ignition.
Packaging materials	: Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Ethyl acetate (141-78-6)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethyl acetate
ACGIH OEL TWA	1440 mg/m³
	400 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Ethyl acetate
OSHA PEL TWA	1400 mg/m³
	400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

8.2. Appropriate engineering controls

- Appropriate engineering controls
- :
- Ensure good ventilation of the work station. Use general ventilation, local exhaust ventilation, or process enclosure to keep the airborne concentrations below the permissible exposure limits. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
- Environmental exposure controls
- :
- Avoid release to the environment. Take measures to reduce or limit air emissions and releases to soil and the aquatic environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Personal protective equipment should be chosen according to national standards and in discussion with the supplier of the protective equipment. Wear recommended personal protective equipment.

Hand protection:
Wear protective gloves. Chemically impervious gloves as described by OSHA's hand protection regulations in 29 CFR 1910.138. Butyl rubber, Nitrile rubber, Neoprene protective gloves with a permeation time of 480 minutes for each ingredient of this mixture.
Eye protection:
Wear safety glasses which protect from splashes
Skin and body protection:
Wear fire/flammable resistant/retardant clothing.
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. Use NIOSH approved respirator if ventilation is inadequate. SCBA for emergency responders. Must be used in accordance with an OSHA compliant respiratory protection program.

Personal protective equipment symbol(s):



Luminary Commit Primer

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: Clear
Odor	: Minimal
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 57 °C / 134 °F
Flash point	: -4 °C / -20 °F
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: 30.6 kPa
Relative vapor density at 20°C	: No data available
Relative density	: 0.9
Solubility	: Insoluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 300 cP
Explosion limits	: No data available
Particle characteristics	: No data available

2-Hydroxyethyl methacrylate

Particle characteristics	No data available
--------------------------	-------------------

Ethyl acetate

Particle characteristics	No data available
--------------------------	-------------------

2,2-bis-(4-(2-hydroxy-3-methacryloxypropoxy) BIS-GMA

Particle characteristics	No data available
--------------------------	-------------------

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

Luminary Commit Primer

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

10.2. Chemical stability

May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Incompatible materials.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Nitrates. Peroxides.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates: Carbon dioxide. Carbon monoxide. Nitrogen oxides.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

2-Hydroxyethyl methacrylate

LD50 oral	5564 mg/kg weight
LD50 dermal	> 5000 mg/kg weight

Ethyl acetate

LD50 oral	4934 mg/kg weight
LD50 dermal	> 20000 mg/kg weight
LC50 Inhalation	4000 mg/l

Skin corrosion/irritation : Not classified

2-Hydroxyethyl methacrylate

Additional information	Repeated or prolonged contact may cause skin irritation
------------------------	---

Ethyl acetate

Skin corrosion/irritation	Negative, Mildly irritating
---------------------------	-----------------------------

Serious eye damage/irritation : Causes serious eye damage.

2-Hydroxyethyl methacrylate

Serious eye damage/irritation	Mildly irritating
-------------------------------	-------------------

Ethyl acetate

Serious eye damage/irritation	Severely irritating to the eyes
-------------------------------	---------------------------------

Respiratory or skin sensitization : May cause an allergic skin reaction.

Luminary Commit Primer

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

2-Hydroxyethyl methacrylate

Skin sensitization	Skin sensitizer
--------------------	-----------------

Ethyl acetate

Maximization test	Not sensitive
-------------------	---------------

Germ cell mutagenicity	: Not classified
------------------------	------------------

Carcinogenicity	: Not classified
-----------------	------------------

Reproductive toxicity	: Not classified
-----------------------	------------------

STOT-single exposure	: May cause drowsiness or dizziness.
----------------------	--------------------------------------

Ethyl acetate

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

2-Hydroxyethyl methacrylate

LOAEC (inhalation,gas,90 days)	350 ppm
--------------------------------	---------

NOAEC (inhalation,gas,90 days)	100 ppm
--------------------------------	---------

Ethyl acetate

LOAEL (oral,90 days)	3600 mg/kg weight
----------------------	-------------------

NOAEL (oral,90 days)	900 mg/kg weight
----------------------	------------------

Aspiration hazard	: Not classified
-------------------	------------------

Luminary Commit Primer

Viscosity, kinematic	No data available
----------------------	-------------------

2-Hydroxyethyl methacrylate

Viscosity, kinematic	No data available
----------------------	-------------------

Ethyl acetate

Viscosity, kinematic	No data available
----------------------	-------------------

2,2-bis-(4-(2-hydroxy-3-methacryloxypropoxy) BIS-GMA

Viscosity, kinematic	No data available
----------------------	-------------------

Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
-----------------------------------	--------------------------------------

Symptoms/effects after skin contact	: May cause an allergic skin reaction. May cause skin irritation.
-------------------------------------	---

Symptoms/effects after eye contact	: Serious damage to eyes. Stinging, redness, itching, tears, blurred vision, swelling.
------------------------------------	--

Symptoms/effects after ingestion	: May cause irritation to the digestive tract.
----------------------------------	--

Most Important Symptoms/Effects	: Risk of serious damage to eyes.
---------------------------------	-----------------------------------

Luminary Commit Primer

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	:	The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	:	Not classified
Hazardous to the aquatic environment, long-term (chronic)	:	Not classified

2-Hydroxyethyl methacrylate

LC50 - [1]	> 100 mg/l
EC50 - [1]	380 mg/l
EC50 72h - Algae [1]	836 mg/l
EC50 72h - Algae [2]	345 mg/l
LOEC (chronic)	49.6 mg/l
NOEC (chronic)	24.1 mg/l

Ethyl acetate

LC50 - [1]	230 mg/l
NOEC (chronic)	2.4 mg/l

12.2. Persistence and degradability

Luminary Commit Primer

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

2-Hydroxyethyl methacrylate

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Ethyl acetate

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

2,2-bis-(4-(2-hydroxy-3-methacryloxypropoxy) BIS-GMA

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential

Ethyl acetate

Bioaccumulative potential	Bioaccumulation unlikely.
---------------------------	---------------------------

12.4. Mobility in soil

No additional information available

Luminary Commit Primer

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

12.5. Other adverse effects

Ozone	:	Not classified
Fluorinated greenhouse gases	:	No

SECTION 13 Disposal considerations

Regional waste regulation	:	Disposal must be done according to official regulations.
Waste treatment methods	:	Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	:	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	:	Disposal must be done according to official regulations. Dispose of this material and its container at hazardous or special waste collection point. Refer to all applicable national, international and local regulations or provisions.
Additional information	:	Flammable vapors may accumulate in the container. Do not re-use empty containers.
Ecological waste information	:	Avoid release to the environment.

SECTION 14 Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
UN1173	1173	1173
14.2. Proper Shipping Name		
Ethyl acetate	ETHYLACETATE	Ethyl acetate
14.3. Transport hazard class(es)		
3	3	3
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
	Marine pollutant: No	
No supplementary information available		

14.6. Transport in bulk

Not applicable

Luminary Commit Primer

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

14.7. Special precautions for user

DOT

UN-No. (DOT)	: UN1173
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

IMDG

Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	: B
Flash point (IMDG)	: -4°C c.c.
Properties and observations (IMDG)	: Colorless liquid with a fragrant odor. Flashpoint: -4°C c.c. Explosive limits: 2.18% to 11.5%. Immiscible with water.

IATA

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
ERG code (IATA)	: 3L

Luminary Commit Primer

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:		
2,2-bis-(4-(2-hydroxy-3-methacryloxypropoxy) BIS-GMA	CAS-No. 1565-94-2	≤ 10%

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Ethyl acetate (141-78-6)

CERCLA RQ	5000 lb
-----------	---------

15.2. International regulations

CANADA

2-Hydroxyethyl methacrylate (868-77-9)

Listed on the Canadian DSL (Domestic Substances List)

Ethyl acetate (141-78-6)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

2-Hydroxyethyl methacrylate (868-77-9)

Listed on INSQ (Mexican National Inventory of Chemical Substances)
--

Ethyl acetate (141-78-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)
--

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Ethyl acetate(141-78-6)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Luminary Commit Primer

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Revision date : 4/24/2025

Issue date : 9/24/2024

Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapor
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

Indication of changes:
HazCom 2024. Emergency number.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.